

Project Name	Type
Catalog #	Date

CITYSAVER® HOUSE SIDE SHIELD

CRS HSS



FEATURES

- Significantly reduces backlight to minimize light trespass.
- Available for Type II Medium (2M), Type III Medium (3M) and Type IV Short (4S) optics.
- Factory installed as an option when ordered with the luminaire.
- Field installable (tool-free) when ordered as a separate accessory.

CONSTRUCTION

- Low-profile, precision fabricated CNC design.
- Flat black TGIC-polyester powder coat finish using tightly controlled multi-stage process to a uniform 3 mil thickness (min). This finish provides superior protection from corrosion and maximum environmental durability.


DIMENSIONS

- 11.38" L x 3.88" W x 0.4" H • 0.33 lbs


IES DISTRIBUTION TYPES

ISO Lines Distance in Units of Mounting Height Values Based on 25 Foot Mounting Height


Type II Medium + HSS



Type III Medium + HSS



Type IV Short + HSS



PHOTOMETRIC DATA

4000K CCT

Model	Optic Type + HSS	IES Report	BUG Rating	Lumens	System Watts	Lm/W
CSR-S-052	TYPE II M	ATAL020691	B0-U0-G1	4170	55.2	75.5
CSR-S-052	TYPE III M	ATAL020692	B1-U0-G1	3962	55.2	71.8
CSR-S-052	TYPE IV S	ATAL020693	B0-U0-G1	3996	55.1	72.5
CSR-M-096	TYPE II M	ATAL020368	B1-U0-G2	7922	106.9	74.1
CSR-M-096	TYPE III M	ATAL020370	B1-U0-G2	8223	107.0	76.9
CSR-M-096	TYPE IV S	ATAL020372	B1-U0-G2	7653	106.8	71.7
CSR-M-150	TYPE II M	ATAL020369	B1-U0-G3	11421	155.8	73.3
CSR-M-150	TYPE III M	ATAL020371	B1-U0-G2	12001	155.9	77.0
CSR-M-150	TYPE IV S	ATAL020373	B0-U0-G1	11264	155.8	72.3

ORDER LOGIC

CSR	-	HSS	-	
	ACCESSORY		SIZE	
HSS	House Side Shield	1	Small	36W/52W
		2	Medium	75W/96W
		3	Medium	125W/150W

