

Project Name	Type
Catalog #	Date

DECORATIVE OUTDOOR LED EMERGENCY UNIT

EMX0029/0044



APPLICATIONS

- Building Entrances/Exits

APPROVALS

- UL Listed for wet locations (0°C - 50°C).
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.

FEATURES

- Long-life, efficient ultra-bright white LED.
- 5 W LED per unit.
- Mirror-bright reflector and prismatic polycarbonate refractor.
- Optional cold-weather unit available for use in freezer applicatoinis (-20°C - 40°F).

HOUSING

- Decorative, low-profile, architectural design.
- Die-cast aluminum housing.
- Durable powder-coated finishes in white, black and dark bronze.
- Sealed and gasketed.

MOUNTING

- Surface mount via quick-connect back plate, which fits most standard junction boxes.
- Universal K/O pattern on back plate for wall mount.

ELECTRICAL

- Dual 120/277 voltage standard.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 4.8V long life, maintenance-free, rechargeable NiCd battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED lamp heads for minimum 90- minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.
- Self-dianostic test feature continually diagnoses units performance and tests system to ensure reliable operation and to meet electrical and life safety codes.

WARRANTY

- 5-year warranty on all electronics and housing.
- Batteries pro rated for five years.

ORDER LOGIC

SAMPLE CATALOG NUMBER: EMX0044

EMX

MODEL	HOUSING COLOR	OPTIONS	COLD WEATHER OPTION
0029	White	Self Diagnostics	Available
0044	Dark Bronze	Self Diagnostics	Available



LED EMERGENCY LIGHT

EMX0029/0044

DIMENSIONAL DATA

